10

15

CLAIMS

1. Process for calculating the position of a mobile station (MS) belonging to a cellular radiocommunication system, starting from an identifier of a current geographic cell in which the said mobile station is located,

characterized in that it includes the following steps:

- calculate a modelled geographic representation (5) of the current cell;
- calculate the barycentre (6) of the said modelled geographic representation of the current cell;
- calculate an uncertainty area (7), with a predetermined geometric shape, centred on the said barycentre and the area of which is approximately equal to the area of the said modelled geographic representation of the current cell;
- and in that the position of the mobile station is defined by the said barycentre, with an uncertainty equal to the said uncertainty area.
- 2. Process according to claim 1, characterised in that the said calculation of a modelled geographic representation (5) of the current cell consists of using a radio prediction tool to calculate a set of points in which the radio frequency field in the current cell is stronger than that in other cells.

- 3. Process according to either of claims 1 or 2, characterised in that the said geometric shape belongs to the group comprising;
 - diaks;
- 5 polygons, preferably hexagons, squares and equilateral triangles..
 - 4. Process according to either of claims 1 or 2, characterised in that the said geometric shape is a polygon
- and in that the said polygon is oriented along the largest direction of the current cell.
 - 5. Process according to any one of claims 1 to 4, characterised in that the position of the mobile station is calculated dynamically.
- 6. Process according to any one of claims 1 to 5, characterised in that it comprises a prior step to extract the identifier of the current cell from at least one signal message dirculating on the radiocommunication system network.
- 7. Process according to claim 6, characterised in that the said extraction is triggered if at least one of the following conditions is satisfied when the mobile station makes a call:
- the number of the mobile station belongs to a predetermined list of calling numbers;
 - the number called by the mobile station belongs to a predetermined list of called numbers;
 - the current cell belongs to a predetermined list of cells.
 - 8. Process according to any one of claims 1 to 7, characterised in that the position of the mobile station and the associated uncertainty are input into a positioning database (2) so that at least one geodependent service can be provided.
- 9. Device (1) for calculating the position of a mobile station belonging to a cellular

30

radiocommunication system starting from the identifier of a current geographic cell in which the said mobile station is located,

characterized in that it comprises:

- 5 means of calculating a modelled geographic representation (5) of the current cell;
 - means of calculating the barycentre (6) of the said modelled geographic representation of the current cell;
- 10 means of calculating an uncertainty area (7), with a predetermined geometric shape centred on the said barycentre and the area of which is approximately equal the area of the said modelled geographic representation of the current cell;
- the position of the mobile station being defined by the 15 said barycentre with an uncertainty equal to the said uncertainty area.
 - 10. Process according to claim 9, characterised in that it is integrated into a radio frequency planning tool (4) for the geographic cells in the said cellular radiocommunication system.
 - 11. Computer program comprising portions / means / program code instructions for execution of the steps in the process according to any one of claims 1 to 8 when the said program is executed on a computer.
 - 12. Computer program intended for calculating the position of a \setminus mobile station (MS) belonging to a cellular radiocommunication system starting from identifier of a current geographic cell in which the said mobile station is located, the said computer program comprising portions / means / program code instructions recorded $o_{\mathbf{k}}$ a medium that can be used in a computer, comprising:
- programming means that can be read by a computer 35 perform the calculat on step for a geographic representation (5) $\sqrt{}$ f the current cell;

20

25

30

bular

5

10

- programming means that can be read by a computer to perform the calculation step to determine the barycentre (6) of this said modelled geographic representation of the current cell;

- programming means that can be read by a computer to perform the calculation step to determine an uncertainty area (7) with a predetermined geometric shape centred on the said barycentre and the area of which is approximately equal to the area of the said modelled geographic representation of the current cell; the position of the mobile station being defined by the barycentre, with an uncertainty equal to the uncertainty area.

add a5